TRANSPARENT LED SCREENS

POLET LED

Technical Specification

POLET Ph 3.9 Pro Indoor (T3.9 Pro)		
Distance Between Pixels (mm)	3.9	
Number of Pixels on m²	65 536	
Brightnes (cd/m²)	5500 nits	
HUE Color Saturnation	R: G: B = 30%:60%:10%	
Color Scale	3,500° — 9,500°K	
Contrast	4,500:1	
Projected IC Mode	1/5	
Angel of View (Level 50% Brightnes)	Horizontal: 140° (70° from center); Vertical: 140° (70° from center)	
Led Diod Brand	Nationstar/Kinglight	
Refresh Rate	1920-3840Hz	
Ingress Protection Rating	IP 65	
Led Procesor (IC)	INCN 2039	
LED Life Time (on 50% Brightnes)	80,000 hours	
Color Deepness	16 bit	
Working Temperature	-30~+65'	
Power	240 V AC single-faze (50-60Hz)	
Power Consumption (W/SQM)	650	
Average Power Consumption (W/SQM)	350	
Modul Configuration	Lenght	64
	Height	64
Modul Dimension (mm)	Lenght	250
	Height	250
Number of Cabinets	Lenght	1
	Height	1
Screen Dimension (mm)	Lenght	1000
	Height	1000
	Deepness	0.1
Recommended Screen View Distance (m)	Min	4
	Max	250
Screen Resolution	Lenght	256
	Height	256
Aspect Ratio H:V	1:1	