

Technical Specification

POLET Ph 7.8 Pro Indoor (T 7.8 Pro)		
Distance Between Pixels (mm)	7.8	
Number of Pixels on m ²	16 384	
Brightnes (cd/m ²)	1000 nits	
HUE Color Saturation	R: G: B = 30%:60%:10%	
Color Scale	3,500° – 9,500°K	
Contrast	4,500:1	
Projected IC Mode	1/32	
Angel of View (Level 50% Brightnes)	Horizontal: 140° (70° from center); Vertical: 140° (70° from center)	
Led Diod Brand	Nationstar/Kinglight	
Refresh Rate	1920-3840	
Ingress Protection Rating	IP 25	
LED Life Time (on 50% Brightnes)	80,000 hours	
Signal Path	Horizontal	
Working Temperature	-30~+65'	
Power	240 V AC single-faze (50-60Hz)	
Power Consumption (W/SQM)	650	
Average Power Consumption (W/SQM)	350	
Modul Configuration	Lenght	32
	Height	32
Modul Dimension (mm)	Lenght	250
	Height	250
Number of Cabinets	Lenght	1
	Height	1
Screen Dimension (mm)	Lenght	1000
	Height	1000
	Deepness	0.1
Recommended Screen View Distance (m)	Min	8
	Max	250
Screen Resolution	Lenght	128
	Height	128
Aspect Ratio H:V	1:1	